

**EVERISING**

# **HEAVY DUTY BAND SAWS -FOR STRUCTURAL STEEL CUTTING**


Mitre Cutting H-1060M

Straight Cutting H-1060S




Model: **H-1060M**

## FLOOR PLAN



## ADVANTAGES OF ANGLED BLADE

- Fewer teeth contact material resulting in better penetration and faster smoother cutting.
- Longer blade life.



## SPECIFICATION

Capacity	鋸切能力	90°	<input type="radio"/> 710 mm (28") <input type="checkbox"/> 1000 x 650mm (40" x 26") W x H
		75°	<input type="radio"/> 710 mm (28") <input type="checkbox"/> 900 x 700 mm (36" x 27") W x H
		60°	<input type="radio"/> 710 mm (28") <input type="checkbox"/> 800 x 700 mm (32" x 27") W x H
		45°	<input type="radio"/> 550 mm (22") <input type="checkbox"/> 550 x 700 mm (22" x 27") W x H
Blade Speed	鋸帶速度	25-35-45-55-65-80 m/min. (82-115-150-180-215-265 fpm) OPTION: 15 to 75 m/min. Variable (50 to 250 fpm)	
Blade Size	鋸帶尺寸	8300 x 50 x 1.6 mm (327" x 2" x .063")	
Motors	馬達	Blade drive 7.5 kw (10 hp) Hydraulic pump 2.2 kw (3 hp) Coolant pump 0.2 kw (1/4 hp) Turn base 0.75 kw (1 hp)	
Guide Arm adjustment	導臂調整方式	Hydraulic	
Blade Tension	鋸帶張力	Hydraulic	
Machine Weight	重量	5500 kgs (12100 lbs)	

## STANDARD FEATURES:

- Positive hydraulic down feed
- Power driven blade cleaning brush.
- Vibration dampening bar
- Hydraulic blade tension
- Idler wheel motion detector with blade stalling and breakage shutoff
- Hydraulically actuated carbide blade guides
- Blade degrees from horizontal
- Movable guide arm with hydraulic lock
- Powered turn base (H-1060M only)

## OPTIONAL EQUIPMENT:

- Variable blade speeds
- Dead roller conveyor
- Powered roller conveyor

## 合濟工業股份有限公司 EVERISING MACHINE CO.

23, 8TH RD. TAICHUNG IND. PARK  
 TAICHUNG 40707, TAIWAN ROC  
 TEL: 886-4-3593178  
 FAX: 886-4-35934110  
 TLX: 57516 EVRS